


sabena [®] B707	Module: LH WING + FL CTR	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : *LUBE*	Issuer : A43710	Cert.St.: 24828	31I0000502
Spec. : MECHANIC	Release Date: 11.10.2001		Page 1 of 2	


AIL TRIM CTRL MECHANISM LUB

				MAINT	RII/INSP
Execution / Start Date:					
End Date:					

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	FL & CH	MIL-L-7870		INSTRUMENT OIL	0.00	

--	--	--	--	--	--	--

AIL TRIM CTRL MECHANISM LUB

sabena B707	Module: LH WING + FL CTR	A/C Reg :	Check :	 31I0000502 Page 2 of 2
	Oper. : RT-MP LC	Issuer : A43710	Cert.St.: 24828	
	Type : *LUBE*	Release Date: 11.10.2001		
	Spec. : MECHANIC			

AIL TRIM CTRL MECHANISM LUB

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		S	MEC	MMS-328 271000 01101 rev 15/05/01 MMS-328 271000 01201 rev 15/05/01		
Check: C						
Zones: 583						
Access: 1360L						

LH WING, LUBRICATE THE INB AILERON TRIM CTRL MECHANISM & SPRING CARTRIDGE & OIL CAPS.

Perform lubrication of the INB AILERON TRIM CTRL MECHANISM & SPRING CARTRIDGE & OIL CAPS.

1. INB AIL TRIM MECHANISM: Apply oil MIL-L-7870 to oil caps (2 places). See fig. item 1.
2. INB AIL TRIM CTRL MECHANISM SPRING CARTRIDGE & OIL CAPS:
 - Remove filler plug, cover drain hole with tape. See fig. item 2.
 - Fill cartridge with oil MIL-L-7870 and exercise cartridge by moving the tab.
 - Remove tape and allow oil to drain out.
 - Reinstall filler plug and lockwire. See fig. item 2.

