



<b>sabena</b> <b>B707</b>	Module: RH WING + FL CTR	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : *LUBE*	Issuer : A43710	Cert.St.: 24828	4110000502
Spec. : MECHANIC	Release Date: 11.10.2001		Page 1 of 2	

**AIL TRIM CTRL MECHANISM LUB**

Execution / Start Date:	
End Date:	

**MAINT**      **RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	FL & CH	MIL-L-7870		INSTRUMENT OIL	0.00	

<b>sabena</b> B707	Module: RH WING + FL CTR	A/C Reg :	Check :	 4110000502 Page 2 of 2
	Oper. : RT-MP LC	Issuer : A43710	Cert.St.: 24828	
	Type : *LUBE*	Release Date: 11.10.2001		
	Spec. : MECHANIC			

**AIL TRIM CTRL MECHANISM LUB**

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		S	MEC	MMS-328 271000 01102 rev 15/05/01 MMS-328 271000 01202 rev 15/05/01		
<b>Check:</b> C						
<b>Zones:</b> 686						
<b>Access:</b> 1360R						

**RH WING, LUBRICATE THE INB AILERON TRIM CTRL MECHANISM & SPRING CARTRIDGE & OIL CAPS.**

Perform lubrication of the INB AILERON TRIM CTRL MECHANISM & SPRING CARTRIDGE & OIL CAPS.

1. INB AIL TRIM MECHANISM: Apply oil MIL-L-7870 to oil caps (2 places). See fig. item 1.
2. INB AIL TRIM CTRL MECHANISM SPRING CARTRIDGE & OIL CAPS:
  - Remove filler plug, cover drain hole with tape. See fig. item 2.
  - Fill cartridge with oil MIL-L-7870 and exercise cartridge by moving the tab.
  - Remove tape and allow oil to drain out.
  - Reinstall filler plug and lockwire. See fig. item 2.

