


sabena B707	Module: COCKPIT + WINDOW	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : MEC-INSP	Issuer : A43710	Cert.St.: 24828	81F2000508
Spec. : MECHANIC	Release Date: 16.10.2001		Page 1 of 2	


FLAP CONT LEVER FORCE CHECK & LUB

			MAINT	RII/INSP
Execution / Start Date:				
End Date:				

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	FL & CH	MIL-G-23827		GREASE	0.00	
1	TOOL	P-154A		SPRING SCALE	0.00	

--	--	--	--	--	--	--

FLAP CONT LEVER FORCE CHECK & LUB

sabena B707	Module: COCKPIT + WINDOW	A/C Reg :	Check :	 81F2000508
	Oper. : RT-MP LC			
	Type : MEC-INSP	Issuer : A43710	Cert.St.: 24828	Page 2 of 2
Spec. : MECHANIC	Release Date: 16.10.2001			

FLAP CONT LEVER FORCE CHECK & LUB

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		M2 S	MEC	MM 27-16-0* rev . MMS-328 275012 00100 rev 15/05/01 MPD 04-27-24 rev .		
Check: C1						
Zones:						
Access:						

FLAP CONTROL LEVER OPERATING FORCE CHECK & LUBRICATION.

1. Check that tangential force required to move flap control lever between detent does not exceed 3 1/2 pounds. Measure force at end of lever with spring scale.

MEASURED FORCE:POUNDS.

2. Lubricate flap control lever: Apply a light film to sliding surface of handle.

