


sabena [®] B707	Module: COCKPIT + WINDOW	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : *LUBE*	Issuer : A43710	Cert.St.: 24828	81I0000503
Spec. : MECHANIC	Release Date: 16.10.2001		Page 1 of 2	


STAB TRIM FWD MECH LUB

Execution / Start Date:	
End Date:	

MAINT **RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	FL & CH	AEROSHELL 17		GREASE	0.00	
1	FL & CH	AEROSHELL 7A		GREASE	0.00	

STAB TRIM FWD MECH LUB

sabena B707	Module: COCKPIT + WINDOW	A/C Reg :	Check :	 81I0000503
	Oper. : RT-MP LC	Issuer : A43710	Cert.St.: 24828	
	Type : *LUBE*	Release Date: 16.10.2001	Page 2 of 2	
Spec. : MECHANIC				

STAB TRIM FWD MECH LUB

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		S	MEC	MMS-328 274001 00100 rev 15/05/01		
Check: C2						
Zones: 221, 222						
Access:						

COCKPIT, STABILIZER TRIM FWD MECHANISM LUBRICATION.

1. INDICATOR FLEXIBLE DRIVE SHAFT: Apply light coat aeroshell grease 7A to total screw. Cycle mechanism several times and wipe off excess lubricant.
2. STABILIZER TRIM CHAIN ASSEMBLY AND SPROCKETS: Apply light coat of aeroshell grease17 (all points). Cycle mechanism twice and wipe off excess.

