



sabena B707	Module: CABIN + WINDOWS	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : *DETAIL CLEAN*	Issuer : A43710	Cert.St.: 24828	91D0000502
Spec. : CABIN	Release Date: 11.10.2001		Page 1 of 2	

AFT LH TOILET CLEAN & DISINFECT

Execution / Start Date:	
End Date:	

MAINT **RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	FL & CH	Cee Bee ALKO		Cleaning Agent	0.00	
1	FL & CH	HAC		Disinfecting Agent	0.00	

sabena B707	Module: CABIN + WINDOWS	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : *DETAIL CLEAN*	Issuer : A43710	Cert.St.: 24828	91D0000502
Spec. : CABIN	Release Date: 11.10.2001		Page 2 of 2	

AFT LH TOILET CLEAN & DISINFECT

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		S	CAB	MMS-328 383003 00103 rev 15/05/01		
Check: B						
Zones: 229						
Access:						

AFT TOILET LH:

PERFORM CLEANING & DISINFECTION OF LAVATORIE FLUSH SYSTEM

PROCEDURE: (SN TECHN. STD MANUAL 4724)

A. CLEANING:

1. Drain waste tank.
2. Fill up the waste tank with the "Prime charge" amount of water.
3. Add Cee Bee ALKO at the rate of 1 liter ALKO to 2 liters of water via the toilet bowl.
4. Operate all flush switches at least 5 times to ensure contact of ALKO solution with all areas.
5. Repeat step 4 several times during the next 2 hours.
6. Drain the waste tank.
7. Rinse the toilet system by filling the waste tank up to 1/2 of its full capacity & operating all flush sw's at least 5 times.
8. Drain the waste tank.

B. DISINFECTION:

1. Fill up the waste tank with the "Prime charge" amount of water.
2. Add HAC at the rate of 10 ml HAC to 1 liter of water via the toilet bowl.
3. Operate all flush sw's at least 5 times to ensure contact of HAC with all areas.
4. Repeat step 3 after 1/2 hour.
5. After another 1/2 hour drain the waste tank