



<b>sabena</b> <sup>®</sup> <b>B707</b>	Module: CABIN + WINDOWS	A/C Reg :	Check :	 <b>91F1000504</b>
	Oper. : RT-MP LC			
	Type : REI-INSP	Issuer : A59513	Cert.St.: 46928	<b>Page 1 of 2</b>
Spec. : REI INSP	Release Date: 31.01.2007			

**FIRE EXT BOTTLE WEIGHT CHECK**

Execution / Start Date:	
End Date:	

MAINT	RII/INSP

<b>sabena</b> B707	Module: CABIN + WINDOWS	A/C Reg :	Check :	 <b>91F1000504</b>
	Oper. : RT-MP LC			
	Type : REI-INSP	Issuer : A59513	Cert.St.: 46928	
Spec. : REI INSP	Release Date: 31.01.2007		Page 2 of 2	

**FIRE EXT BOTTLE WEIGHT CHECK**

					MAINT	RII/INSP	
Nr.	Hardtime	Task	Spec.	Related Documents			
1.		E3 M1	INS	FAR 121.308 (A) rev . MMS-328 262702 00102 rev 15/05/01			
<b>Check: C</b>							
<b>Zones: 228</b>							
<b>Access:</b>							
NRC YES <input type="radio"/> NO <input type="radio"/>		IF YES, NUMBER(S): .....					

**AFT LAVATORY RH : FIRE EXTINGUISHING BOTTLE WEIGHT CHECK & DETAILED VISUAL INSPECTION.**

1. Remove bottle at lavatory 'C'
2. Remove bottle at lavatory 'E'
3. Inspect bottle for corrosion, scratches, dents or leakage. Dents deeper than 1/16 inch per inch of average dent diameter or scratches deeper than 0.004 inch are cause for rejection & replacement.
4. Perform weight test: If weight is 20 grams less than weight stated on label, replace bottle.
5. Reinstall bottle at lavatory 'C'.
6. Reinstall bottle at lavatory ' E'.

