



<b>sabena</b> <b>B707</b>	Module: MLG WW + DOORS	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A59513	Cert.St.: 45379	<b>11H1000503</b>
Spec. : MECHANIC	Release Date: 14.07.2008		<b>Page 1 of 3</b>	

**UTILITY HYD SYST RET FILTER REPL**

Execution / Start Date:	
End Date:	

**MAINT      RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	CONSUM	10-60593-2	121218	FILTER	1.00	EA
1	CONSUM	7552496	123990	FILTER	1.00	EA
1	CONSUM	NAS1611-143A	238882	PACKING	2.00	EA
1	CONSUM	NAS1611-214A	024607	PACKING	1.00	EA
1	CONSUM	NAS1611-242A	230654	PACKING	1.00	EA
1	TOOL	L-809A		TORQUEMETER	1.00	EA


<b>sabena</b> <b>B707</b>	Module: MLG WW + DOORS	A/C Reg :	Check :	 <b>11H1000503</b> <b>Page 2 of 3</b>
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A59513	Cert.St.: 45379	
	Spec. : MECHANIC	Release Date: 14.07.2008		

**UTILITY HYD SYST RET FILTER REPL**

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		S	MEC	MMS-328 291001 00100 rev 15/05/01		
<b>Check: C</b>						
<b>Zones: 135</b>						
<b>Access:</b>						
NRC YES <input type="radio"/> NO <input type="radio"/>		IF YES, NUMBER(S): .....				

**UTILITY HYDRAULIC SYSTEM RETURN FILTER REPLACEMENT.**

1. Remove utility system return filter element.
  - Depressurize utility hydraulic system by moving bypass valve handle to "BYPASS". Move handle back to "CLOSED".
  - Depressurize utility reservoir.
  - dispose of element and clean the case.
2. Installation of new filter element.
  - Place new element with two new packings.
  - Position the case and secure it to body with clamp. Torque clamp to 70 -80 pound-inches.
3. With any of the inboard engines operating at "IDDL" CHECK FILTER FOR LEAKS.

<b>sabena</b> B707	Module: MLG WW + DOORS	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A59513	Cert.St.: 45379	11H1000503
	Spec. : MECHANIC	Release Date: 14.07.2008		Page 3 of 3

UTILITY HYD SYST RET FILTER REPL

MAINT RII/INSP

