



<b>sabena</b> <b>B707</b>	Module: ENGINE 2	A/C Reg :	Check :	
	Oper. : RT-MP LC	Issuer : A59513	Cert.St.: 45379	
	Type : MEC-INSP	Release Date: 21.11.2007	Page 1 of 3	
Spec. : MECH. INSP				

**ENG 2 IGNITER PLUG INSP**

Execution / Start Date:	
End Date:	

**MAINT**      **RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	TOOL	TO 600 POUND INCHES		TORQUEMETER	0.00	


<b>sabena</b> <b>B707</b>	Module: ENGINE 2	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : MEC-INSP	Issuer : A59513	Cert.St.: 45379	<b>O1F2000504</b>
Spec. : MECH. INSP	Release Date: 21.11.2007		<b>Page 2 of 3</b>	

**ENG 2 IGNITER PLUG INSP**

					MAINT	RII/INSP	
Nr.	Hardtime	Task	Spec.	Related Documents			
1.		E3 S	INS	MMS-328 740002 A0102 rev 15/05/01			
<b>Check: B</b>							
<b>Zones: 452</b>							
<b>Access:</b>							
NRC YES <input type="radio"/> NO <input type="radio"/>		IF YES, NUMBER(S): .....					

**IGNITER PLUGS INSPECTION:**

1. Remove the two plugs.
2. INSPECT: The two plugs – scrap when found CRACKED or excessively ERODED.
  - PLUG 1.
  - PLUG 2.
- 3.a) Install the two igniter plugs & torque plugs to **300 – 360 POUND-INCHES**.
  - b) Install igniter lead & torque connector to **140 – 160 POUND-INCHES**.  
(Taking care not to twist the lead).
  - PLUG 1.
  - PLUG 2.

<b>sabena</b> B707	Module: ENGINE 2	A/C Reg :	Check :	 <b>O1F2000504</b>
	Oper. : RT-MP LC	Issuer : A59513	Cert.St.: 45379	
	Type : MEC-INSP	Release Date: 21.11.2007	<b>Page 3 of 3</b>	

**ENG 2 IGNITER PLUG INSP**

**MAINT      RII/INSP**

