



<b>sabena</b> <b>B707</b>	Module: ENGINE 4	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A43710	Cert.St.: 24828	<b>Q1H1000505</b>
Spec. : MECHANIC	Release Date: 17.10.2001		<b>Page 1 of 3</b>	

**ENG #4 CSD OIL FILTER REPL**

Execution / Start Date:	
End Date:	

**MAINT**      **RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	CONSUM	7578137-101	347239	FILTER	1.00	EA
1	CONSUM	7583142	346746	FILTER	1.00	EA
1	CONSUM	M 83248-1-014	421691	O RING	1.00	EA
1	CONSUM	M 83248-1-018	287842	O RING	1.00	EA
1	CONSUM	M 83248-1-128	287810	O RING	1.00	EA
1	CONSUM	MS 28782-19	865540	O RING	1.00	EA
1	CONSUM	MS 9388-214	548335	O RING	1.00	EA
1	CONSUM	MS 9388-228	291425	O RING	1.00	EA
1	FL & CH	28 075 3442		ACRYLOID HF 825	0.00	
1	FL & CH	28 033 1002		VASELINE	0.00	
1	TOOL	L-452A	150510	TORQUEMETER	1.00	EA
1	TOOL	L-465A	150508	TORQUEMETER	0.00	

<b>sabena</b> <b>B707</b>	Module: ENGINE 4	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A43710	Cert.St.: 24828	<b>Q1H1000505</b>
	Spec. : MECHANIC	Release Date: 17.10.2001		<b>Page 2 of 3</b>

**ENG #4 CSD OIL FILTER REPL**

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		S	MEC	MMS-328 241003 00104 rev 15/05/01		
Check: C						
Zones: 454						
Access:						

**NOTE: FILTER REPLACEMENT MUST BE PERFORMED TOGETHER WITH CSD OIL CHANGE REF. MS: 241002 00101**

**CSD OIL FILTERS REPLACEMENT.**

**CSD LINE FILTER REPLACEMENT:**

1. Remove LINE OIL FILTER.
  - Remove locking wire.
  - Unscrew filter case & discard case O-ring.
  - Remove filter element & discard filter O-ring.
2. Install LINE OIL FILTER.
  - Replace filter O-ring inside mounth of filter element.
  - Replace filter element.
  - Coat filter thread with small amount of VASELINE.
  - Using new case O-ring, install filter case & tighten to 120-360 pound-inches & lockwire.

