



<b>sabena</b> <b>B707</b>	Module: ENGINE 4	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A59513	Cert.St.: 50516	<b>Q1H1000507</b>
Spec. : MECHANIC	Release Date: 19.05.2010		<b>Page 1 of 2</b>	

**ENG #4 FUEL FILT DIFF PRESS SW REPL**

Execution / Start Date:	
End Date:	

**MAINT**      **RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	CONSUM	MS 9967-007	424687	PACKING	1.00	EA
1	CONSUM	MS 9967-008	549520	PACKING	1.00	EA
1	CONSUM	MS 9021-005	865753	SEAL	2.00	EA
1	CONSUM	377102	120281	SWITCH ASSY	1.00	EA

<b>sabena</b> <b>B707</b>	Module: ENGINE 4	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A59513	Cert.St.: 50516	<b>Q1H1000507</b>
	Spec. : MECHANIC	Release Date: 19.05.2010		<b>Page 2 of 2</b>

**ENG #4 FUEL FILT DIFF PRESS SW REPL**

					MAINT	RII/INSP	
Nr.	Hardtime	Task	Spec.	Related Documents			
1.		S	MEC	MMS-328 731002 A0204 rev 06.06.02			
Check: C							
Zones: 454							
Access:							
NRC YES <input type="radio"/> NO <input type="radio"/>		IF YES, NUMBER(S):					

**ENGINE #4 FUEL FILTER DIFFERENTIAL PRESSURE SWITCH REPLACEMENT.**

**1. REMOVAL:**

- Disconnect electrical leads.
- Remove 4 bolts & washers securing differential fluid pressure switch to fuel de-icing filter cover & remove switch.

**2. INSTALLATION:**

- Install (replaced) differential fluid pressure switch & secure with 4 bolts & washers.
- Torque & lockwire bolts.
- Connect electrical leads.

**3. CHECK FOR LEAKS.**

