



<b>sabena</b> <b>B707</b>	Module: PYLON 2	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A43710	Cert.St.: 24828	<b>T1H1000503</b>
Spec. : MECHANIC	Release Date: 17.10.2001		<b>Page 1 of 2</b>	

**ENG #2, 3, 4 T/C OIL FILT REPL**

Execution / Start Date:	
End Date:	

**MAINT**      **RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	CONSUM	6660141	125350	FILTER	3.00	EA
1	CONSUM	S8057AK17	125351	PACKING	3.00	EA
1	CONSUM	S8171AE5	125349	PACKING	3.00	EA

<b>sabena</b> <b>B707</b>	Module: PYLON 2	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A43710	Cert.St.: 24828	<b>T1H1000503</b>
	Spec. : MECHANIC	Release Date: 17.10.2001		<b>Page 2 of 2</b>

**ENG #2, 3, 4 T/C OIL FILT REPL**

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		S	MEC	MMS-328 361008 00100 rev 15/05/01		
<b>Check: C1</b>						
<b>Zones: 452, 453, 454</b>						
<b>Access:</b>						

**ENGINE #2, 3, 4 TURBO COMPRESSOR OIL FILTER REPLACEMENT.**

1. Unscrew filter housing from housing cap.
2. Remove and discard packing rings and filter element.
3. Check filter for contamination.
4. Clean filter housing.
5. Place new filter element in housing.
6. Place new packing ring on filter and new packing ring on filter housing.
7. Screw filter housing into filter cap and lockwire.

PERFORMED ON:

TURBO COMPRESSOR ENG Nr 2.

TURBO COMPRESSOR ENG Nr 3.

TURBO COMPRESSOR ENG Nr 4.