


sabena B707	Module: PYLON 3	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A59513	Cert.St.: 50516	U1H1000500
Spec. : MECHANIC	Release Date: 19.05.2010		Page 1 of 2	


UTILITY HYD PUMP CASE DRAIN FILTER REPL

			MAINT	RII/INSP
Execution / Start Date:				
End Date:				

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	CONSUM	043046	142023	FILTER	1.00	EA
1	CONSUM	NAS1611-012	022299	PACKING	1.00	EA
1	CONSUM	NAS1611-216	220027	PACKING	1.00	EA
1	TOOL	L-809A		TORQUEMETER	1.00	EA

--	--	--	--	--	--	--

UTILITY HYD PUMP CASE DRAIN FILTER REPL

sabena B707	Module: PYLON 3	A/C Reg :	Check :	 U1H1000500 Page 2 of 2
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A59513	Cert.St.: 50516	
	Spec. : MECHANIC	Release Date: 19.05.2010		

UTILITY HYD PUMP CASE DRAIN FILTER REPL

					MAINT	RII/INSP	
Nr.	Hardtime	Task	Spec.	Related Documents			
1.		S	MEC	MMS-328 291009 00104 rev 15/05/01			
Check: C							
Zones: 457							
Access: 1710							
NRC YES <input type="radio"/> NO <input type="radio"/>		IF YES, NUMBER(S):					

HYDRAULIC UTILITY PUMP CASE DRAIN FILTER ELEMENT REPLACEMENT ON PYLON ENG #3.

Replace filter element of the hydraulic utility pump case drain.

1. Removal of filter.

- Depressurize utility reservoir.
- Break lockwire and unscrew filter case and remove case with filter element.
- Remove element and check element and bowl for metal contamination.
- Clean element and filter bowl.

2. Installation of filter.

- Insert packing in filter element and place element in filter case.
- Place packing on filter case and screw filter case into filter head. Torque filter case to 75 pound-inches.
- Lockwire filter case to filter head.

3. Check for leaks at ENGINE RUN UP.

