



sabena B707	Module: PYLON 4	A/C Reg :	Check :	
	Oper. : RT-MP LC			
	Type : SERVICING	Issuer : A43710	Cert.St.: 24828	V1H1000500
Spec. : MECHANIC	Release Date: 17.10.2001		Page 1 of 2	

ENG #4 TURBO COMPRESS DIF PRES REG FILTER CLEAN

Execution / Start Date:	
End Date:	

MAINT **RII/INSP**

Pos	Mat. Type	P/N	IDN	Description	Qty	Unit
1	CONSUM	S8990-113	371633	PACKING	1.00	EA
1	CONSUM	S8990-115	132390	PACKING	1.00	EA
1	FL & CH	P-S-661		SOLVENT	0.00	

sabena B707	Module: PYLON 4	A/C Reg :	Check :	 V1H1000500
	Oper. : RT-MP LC	Issuer : A43710	Cert.St.: 24828	
	Type : SERVICING	Release Date: 17.10.2001	Page 2 of 2	
Spec. : MECHANIC				

ENG #4 TURBO COMPRESS DIF PRES REG FILTER CLEAN

					MAINT	RII/INSP
Nr.	Hardtime	Task	Spec.	Related Documents		
1.		S	MEC	MMS-328 361006 00100 rev 15/05/01		
Check: C						
Zones: 454						
Access: 3703						

ENG #4 TURBO COMPRESSOR DIFFERENTIAL PRESSURE REGULATOR FILTER CLEANING.

REMOVAL:

1. Remove filter element and spring.
2. Wash filter assy in dry-cleaning solvent and dry thoroughly.

INSTALLATION:

1. Remove and replace packing ring in groove of filter housing.
2. Insert spring in deepest counterbore of filter housing.
3. Insert filter element into filter housing with boss facing inwards, ensure spring fits over filter element boss.
4. Tighten plug and lockwire.

